



H2O GL Series

Indirect Water Heaters



**Residential
Limited
Lifetime Warranty
Tank Models
Available**

The Utica Heating GL Series of Single Coil Glass Lined Indirect Water Heaters is an affordable water storage heating solution.

The glass lined indirect water heater offers an affordable solution in areas where high chloride levels in the domestic water supply can corrode a stainless steel tank.

The internal coil delivers unmatched performance with a large surface area resulting in high domestic hot water ratings.

FEATURES

- 5 Sizes Available:
(31, 42, 53, 79, 106 Gallon Capacities)
- Low Pressure Drop
- Magnesium Anode Rod (Corrosion Protection)
- Enameled Coated Steel Tank and Coil
- Minimal Standby Losses
- Flexible Scratch Resistant Jacket
- Aquastat Sensor Well
- Temperature Pressure Relief Valve
- 1" Tappings to Accommodate Higher Flow Rates
- Blue and Red color coded trim rings to identify the supply and return lines.
- Removable top cover plate allows quick access to inspect the tank and anode rod. Makes tank cleaning and anode rod replacement easier.
- Built in tapping for recirculation loop results in less piping for the installer.
- Tank water temperature gauge
- Residential Limited Warranty:
Tank, 7-Years; Parts, 2-Years
- Residential Limited Lifetime Warranty
Tank Models Available
Go to www.uticaboilers.com for details
- Commercial Limited Warranty:
Tank, 5-Years; Parts, 2-Years

H2O Glass Lined Indirect Water Heater

Item Number	Storage Volume	Coil Heating Surface	Dimensions (Inches)		Piping Connections N.P.T.		Approx. Wgt.
	Gallons	Square Feet	Height	Diameter	Domestic Water In/Out	Boiler Water In/Out	(lbs.)
H2OIG40UH	42	14	45	24	1	1	180
H2OIG50UH	53	14	51	24	1	1	200
H2OIG80UH	79	20.7	48	30	1	1	243
H2OIG105UH	106	26	62	30	1	1	393

Item Number	Max. First Hour Rating	Continuous Rating	Boiler Output Needed	Boiler Water Flow Through the Coil	Pressure Drop Through the Coil
	Gal./Hr. @	Gal./Hr. @	MBH	(Gal./Min.)	(Ft. Water)
	115° F	115° F			
H2OIG40UH	198	162	105	14.0	10.7
	256	220	120		
H2OIG50UH	212	169	110	14.0	10.7
	310	268	140		
H2OIG80UH	228	164	110	14.0	15.9
	346	281	180		
H2OIG105UH	270	175	115	14.0	19.7
	440	345	220		

All ratings are based on 180° F boiler water supply temperature. Domestic hot water 70° F rise, 45° F water inlet temperature. Specifications subject to change without notice.

Standard Equipment	Smooth enameled coil, magnesium anode rod and temperature pressure relief valve, Honeywell Aquastat. Water tank temperature gauge.
--------------------	--



Honeywell Aquastat
L4080B1352
(Field installed)



Conforms to UL STD 174
Certified to CAN/CSA STD C22.2
No. 110-94



ECR International, Inc. 2201 Dwyer Avenue, Utica, NY 13501
Tel. 800 253 7900
www.ecrinternational.com

All specifications subject to change without notice.
©2021 ECR International, Inc.
PN 240012395 Rev. [09/10/21]